## **Amendment to the Abstract:**

The Abstract has been amended. A revised Abstract is attached.

## ABSTRACT-OF THE DISCLOSURE

In mounting of order to mount an electronic component for mounting, a connection terminal (5a) of an the electronic component (5) by bonding bonded to electrodes (2) of a substrate (1) by. This is done by using solder paste (4) mixing which mixes solder particles in a thermosetting adhesive, the. The solder paste (4) is supplied to the electrodes (2) and a recess (3) as adhesion reinforcing portion provided in other portion, and solder. Solder print parts (4A, 4B) are formed, and the. The electronic component (5) is mounted, and the connection terminal (5a) and the main body (5b) of the electronic component (5) are adhered to the solder print parts (4A, 4B), and are heated in this state by reflow. As a result, the connection terminal (5a) and the electrodes (2) are bonded by a solder junction (6a), and by the adhesive component of the solder print part (4B), second resin reinforced part (7b) is formed for fixing the main body (5b) and substrate (1).

Respectfully submitted,

Lawrence E. Ashery, Reg. No. 34,515 Attorney for Applicants

LEA/dmw

Attachment:

**Abstract** 

Dated: August 23, 2006

P.O. Box 980 Valley Forge, PA 19482 (610) 407-0700

The Director is hereby authorized to charge or credit Deposit Account No. 18-0350 for any additional fees, or any underpayment or credit for overpayment in connection herewith..

**EXPRESS MAIL** 

Mailing Label Number:

EV 614 759 424 US

Date of Deposit:

August 23, 2006

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-14504

Amanda/Kelly

55585

## **ABSTRACT**

In order to mount an electronic component, a connection terminal of the electronic component is bonded to electrodes of a substrate. This is done by using solder paste which mixes solder particles in a thermosetting adhesive. The solder paste is supplied to the electrodes and a recess . Solder print parts are formed. The electronic component is mounted and the connection terminal and the main body of the electronic component are adhered to the solder print parts, and are heated in this state by reflow. As a result, the connection terminal and the electrodes are bonded by a solder junction.